

APV Technische Produkte GmbH

### APV : ZS 200 M 3

METAREX INOV												
Drehzahl [min <sup>-1</sup> ] (Arbeitsbreite/ Auftreffpunkt)	Schieberstellung											
	9	10	11	12	13	14	15	16	17	18	19	
700 (~10m/-45)	0,31	0,52	0,73	1,05	1,43	1,92	2,24	2,81				
1000 (~16m/-25)			0,80	1,11	1,47	1,85	2,36	2,81	3,36	3,92		
1500 (~21m/0)				1,13	1,49	1,91	2,52	3,10	3,69	4,32	5,06	
2000 (~30m/+45)				1,64	2,14	2,74	3,46	3,89	4,52	5,27	5,86	
Gewicht in kg/min												

HINWEIS: Die in der Streutabelle angegebenen Werte sind nur Richtwerte, da nicht jedes Streugut die gleichen Fließeigenschaften hat. Eine genaue Einstellung des Gerätes kann daher nur mittels einer Abdreprobe erfolgen.

# LEHNER SUPER VARIO

## METAREX INOV Einstellungen

Streumenge : 3kg/ha									
Drehzahl (U/min)	250	400	600	1000	1700	2500	2650	2800	
Arbeitsbreite (m)	3	6	9	12	15	18	21	24	
Wurfschaufelstellung	Loch 2,5	Loch 2,5	Loch 2,5	Loch 2	Loch 2	Loch 2	Loch 2	Loch 2	Loch 2
Geschwindigkeit (km/h)	10	15	16	17	19	20	22	23	24
	11	15	16	18	19	21	22	24	25
	12	15	17	18	20	22	23	25	26
	13	15	17	19	20	22	24	26	28
	14	15	17	19	21	23	25	27	29
	15	15	17	20	22	24	26	28	30
	16	16	18	20	22	24	26	29	31
	17	16	18	20	23	25	27	30	32
	18	16	18	21	23	26	28	31	33
	19	16	19	21	24	26	29	32	34
	20	16	19	22	24	27	30	33	35
	21	16	19	22	25	28	31	33	36
	22	16	19	22	25	28	31	34	37
23	17	20	23	26	29	32	35	39	
24	17	20	23	26	30	33	36	40	
25	17	20	24	27	30	34	37	41	
Streumenge : 4kg/ha									
Drehzahl (U/min)	250	400	600	1000	1700	2500	2650	2800	
Arbeitsbreite (m)	3	6	9	12	15	18	21	24	
Wurfschaufelstellung	Loch 2,5	Loch 2,5	Loch 2,5	Loch 2	Loch 2	Loch 2	Loch 2	Loch 2	Loch 2
Geschwindigkeit (km/h)	10	15	17	19	21	22	24	26	28
	11	15	17	19	21	23	25	27	29
	12	16	18	20	22	24	26	29	31
	13	16	18	20	23	25	28	30	32
	14	16	18	21	24	26	29	31	34
	15	16	19	22	24	27	30	33	35
	16	16	19	22	25	28	31	34	37
	17	16	20	23	26	29	32	35	38
	18	17	20	23	26	30	33	36	40
	19	17	20	24	27	31	34	38	41
	20	17	21	24	28	32	35	39	43
	21	17	21	25	29	33	36	40	44
	22	17	21	25	29	33	37	41	46
23	18	22	26	30	34	39	43	47	
24	18	22	26	31	35	40	44	48	
25	18	22	27	32	36	41	45	50	
Streumenge : 5kg/ha									
Drehzahl (U/min)	250	400	600	1000	1700	2500	2650	2800	
Arbeitsbreite (m)	3	6	9	12	15	18	21	24	
Wurfschaufelstellung	Loch 2,5	Loch 2,5	Loch 2,5	Loch 2	Loch 2	Loch 2	Loch 2	Loch 2	Loch 2
Geschwindigkeit (km/h)	10	16	18	20	22	25	27	29	32
	11	16	18	21	23	26	28	31	33
	12	16	19	22	24	27	30	33	35
	13	16	19	22	25	28	31	34	37
	14	17	20	23	26	29	33	36	39
	15	17	20	24	27	30	34	37	41
	16	17	21	24	28	32	35	39	43
	17	17	21	25	29	33	37	41	44
	18	17	22	26	30	34	38	42	46
	19	18	22	26	31	35	39	44	48
	20	18	22	27	32	36	41	45	50
	21	18	23	28	33	37	42	47	52
	22	18	23	28	33	38	44	49	54
23	19	24	29	34	40	45	50	56	
24	19	24	30	35	41	46	52	57	
25	19	25	30	36	42	48	53	59	